



Lowrance HDS PRO 12 display 12" Active Imaging HD

Code: 000-16003-001

€ 2.569,00 ~~€ 3.292,78~~ - 22%

LOWRANCE

AVAILABLE IN TWO VERSIONS:

Without transducer or With Active Imaging™ HD transom transducer

LOWRANCE HDS PRO 12

Enhance your vision and fish more with the new HDS PRO fishfinder / chartplotter. Watch fish react to your bait with new high-resolution ActiveTarget® 2 Live sonar and locate schools and structures where they hang out with new high-definition Active Imaging™ HD. Find fishing spots quickly with the latest C-MAP® charts using a fully connected fishing system and flawless boat control from bow to stern.

Main functions

SolarMax™ HD touchscreen viewable from any angle and with polarized lenses

Novelty! 1.2 MHz HD High Definition Active Imaging™ Ready (Lowrance CHIRP/SideScan/DownScan Imaging™)

Novelty! Ready for ActiveTarget® 2 Live high-resolution sonar

FishReveal™ with new SideScan view and Downscan view

Screen available in 9", 10", 12" and 16" sizes

Worldwide basemap with the ability to upgrade to C-MAP® DISCOVER and REVEAL or other chart providers.

Real-time mapping available with C-MAP® Genesis Live.

Support for the new ActiveTarget® Scout and Ghost® Trolling Motor 360 chart overlay views

Large programmable keys for 10", 12" and 16" models

Touchscreen control of Power-Pole® anchors, Ghost® Trolling Motor, autopilot and Lowrance outboard pilot

Wireless connectivity, Bluetooth® and NMEA 2000®, plus smartphone notifications

Wide range of optional chart upgrades, including C-MAP® REVEAL, Navionics®, Florida Marine Tracks and more.

SOLARMAX™ HD

The SolarMAX™ HD touchscreen delivers pictures

breathhtaking fish, texture and detail

maps visible from any angle,

under direct sunlight and through lenses

polarized: characteristics that make the

difference in water.

ACTIVE IMAGING™ HD

Active Imaging™ HD, our clearest sonar

ever, offers high-definition views of sonar

Painestore

Indirizzo 47921 Rimini

+39054121629 +39054121732

Url: https://www.painestore.com/lowrance_hds_9_live_display_9_active_imaging_3



Lowrance CHIRP, SideScan and DownScan Imaging™.

MAXIMUM CLARITY

The better the visibility, the better your catches will be.

From the high-definition touchscreen display to the extreme clarity of new optimized Lowrance sonar, the HDS® Pro has it all complete with useful underwater views that will make your fishing experience exceptional.

SPECIFICATIONS

Display

Viewing angles 80° top/bottom, 80° left/right
Pure White LED backlight color
Screen brightness >1200 Nits 1280x800 display resolution

Physicist

Dimensions (height x width x depth) 44 x 17.3 x 39.2 Weight 2.68 kg
Compass safety 12" (300mm)
Mounting Type Gimbal Bracket Front Dash Flush Mount Rear Dash Flush Mount

Connectivity

Bluetooth Integrated Bluetooth 4.0 with support for Bluetooth Classic
NMEA 2000 1x Micro-C connectivity
Wi-Fi Connectivity Item Internal 802.11b/g/n and Compatible with WiFi-1 Module
SD card memory 2 micro SD cards up to 32GB
Ethernet 1x 100 Mbit ports, 6 max MFDs on a network
Video Output: No Input: Composite video RCA - single channel via optional adapter

Cartography

Supported Charts C-MAP Reveal C-MAP Discover C-MAP Reveal XC-MAP Discover XC-MAP (MAX N, MAX N+) C-MAP Genesis C-MAP Precision Contour HD (AMER ONLY) Navionics (Gold, NAV+ Platinum+) Insight (Pro and HD) Lowrance Regional Mapping Partners

Autopilot

Steering Mode Course Heading Waypoint Power Steer Course Heading Waypoint Power Steer U-Turn C-Turn Spiral Zigzag Square Lazy-S

Electric

Maximum Power Consumption 2.9A @ 13.8VDC with Full Backlight, Sonar on
Minimum power consumption 2.0A @ 13VDC with Full Backlight, Sonar on
Typical Power Consumption 2.0A @ 13VDC with Full Backlight, Sonar on
Supply voltage 12V DC (10.8-17VDC)
Recommended fuse rating 3A

Environment

Operating Temperature Range 5°F to 131°F (-15°C to 55°C)
Storage Temperature Range 4°F to 140°F (-20°C to 60°C)
Waterproof Level IPX7 with card door closed Humidity IEC 60945 Damp Heat 150°F (66°C) at 95% Relative Humidity (48 hrs)
Vibration Shock 100,000 cycles of 20 G

GPS

GPS receiver channels 16
DGPS, WAAS correction
Refresh rate 10Hz
Position accuracy 20m RMS
Time before repair 30s

MFD extension

AIS AIS Chart and Radar overlay. Target vessel details.

Painestore

Indirizzo 47921 Rimini
+39054121629 +39054121732

Url: https://www.painestore.com/lowrance_hds_9_live_display_9_active_imaging_3



Autopilot Outboard Pilot NAC-1 NAC-2 Ghost Trolling Motor MotorGuide Xi5/Xi3 Trolling Motor **requires Motorguide PinPoint Gateway

Cartography included C-MAP World Background (ROW models) Navionics basemap (AMER and ROW models)

CzoneNaviop digital switching

Sonar Compatibility Integrated: CHIRP Broadband Active Imaging DownScan Active Imaging SideScan Active Imaging HD DownScan Active Imaging HD SideScan Compatible with: ActiveTarget ActiveTarget2, S3100 SonarHub StructureScan StructureScan HD StructureScan 3D LiveSight (requires PSI-1 module)

GPS 10Hz GPS/GLONASS WAAS/EGNOS/MSAS

Internal memory 8.0 GB Internal

Meteo SiriusXM via WM-3 (USA only) SiriusXM via WM-4 (USA only)

Multimedia SonicHub SonicHub2 FusionLink products any NMEA 2000 compliant Marine Audio products

Waypoints, Routes, Tracks 3000 Waypoints 100 Routes 100 Trails with up to 10,000 points per trail

Other

Interface Touchscreen: Full Multi-touch touchscreen Keypad: 8-way directional keypad Zoom +/- Exit Enter Menu Waypoint Power/Light

Free CMAP

-
-
-
-
-

Caratteristiche

Sei interessato ad una offerta privata?

Display

Painestore

Indirizzo 47921 Rimini

+39054121629 +39054121732

Url: https://www.painestore.com/lowrance_hds_9_live_display_9_active_imaging_3